


recessed spot

Artikel-Nr. 0070.25



recessed spot, alu, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: GX5.3, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, voltage: 12V, Power: max. 50W, amount of light sources / fittings: 1.0 Stk, Adjustability: swivelling, without operating, Type of dimming: other, .

| | |
|--------------------|------------------|
| Artikel-Nr. | 0070.25 |
| price | 25.80 € |
| Stand: | 20.03.2020 06:19 |

| | |
|--------------------------------|-----------|
| Colour | alu |
| amount of light sources / fit- | 1 Qty |
| Type of dimming | other |
| Width | 90 mm |
| Brackets | 5366 |
| Built-in diameter | 75 mm |
| Built-in depth | 55 mm |
| material | Aluminium |
| version | GX5.3 |
| Power | max. 50 W |

| | |
|-----------------------------|---------------------|
| voltage | 12V |
| Lamp type | LV halogen lamp |
| Length | 90 mm |
| circuit type secondary side | parallel conduction |
| IP protection class | IP20 |
| Protection class | III |
| Swivel angle | 30 ° |
| Voltage type | AC |
| Clip | without clip |
| Adjustability | swivelling |