




LED-Einbaudownlight HYBRIDE, V4A, IP67

Artikel-Nr. 12670223



LED-Einbaudownlight HYBRIDE, V4A, IP67, stainless steel. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Stainless steel / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP67, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 9W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 460lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 40°, Adjustability: not adjustable, With operating gear, Type of dimming: switchable, .

Artikel-Nr.	12670223	Applications
price	288.80 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	02.09.2020 01:08	GASTRONOMY
Discount group	Discount group 1	

colour of light	3000 K
Colour	stainless steel
Radiation angle	40 °
amount of light sources / fittings	1 Qty
material	Stainless steel / Aluminium / Glass
Power	9 W
Lamp type	LED
shipping	inkl. Konverter zum Anschluss an 230 V-Netzspannung, schaltbar und 5.000 mm Anschlussleitung
Colour rendering	CRI > 80
Type of dimming	switchable

Built-in width	125 mm
Built-in length	125 mm
Built-in depth	145 mm
voltage	230V AC 50Hz
Luminous flux	460 lm
Impact strength	IK09
IP protection class	IP67
Protection class	I
Voltage type	AC
Adjustability	not adjustable
Length	135 mm
Width	135 mm
Height-depth	126 mm
circuit type secondary side	parallel conduction