



LED-Einbaustrahler, schaltbar  
**Artikel-Nr. 38144633**

Licht.  
 Für Generationen.



Distance (m)	Beam Diameter (m)	Beam Area (m²)
1.0 m	0.710.7	1173.2
2.0 m	1.411.4	2693.3
3.0 m	2.112.0	1304.4
4.0 m	2.812.7	73.3
5.0 m	3.513.4	46.9

LED-Einbaustrahler, schaltbar, champagne, square. In a compact design, for installation in tool-less rapid assembly systems. set incl. driver for 230V. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, voltage: 230V AC 50Hz, Power: 6 W, Luminous flux: 640.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 38.0 °, Adjustability: swivelling, With operating gear: Yes, Type of dimming: switchable, Energy efficiency class: A++ to A,

<b>Artikel-Nr.</b>	<b>38144633</b>	<b>Applications</b>
<b>price</b>	96.80 €	HOME   LIVING OFFICE   COMMUNICATION HOTEL INDUSTRY
<b>Stand:</b>	27.08.2019 14:13	GASTRONOMY

colour of light	3000 K
Colour	champagne
Radiation angle	38 °
amount of light sources /	1 Qty
material	Aluminium / Glass
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	switchable
Built-in diameter	68 mm
Built-in depth	50 mm
voltage	230V AC 50Hz

Luminous flux	640 lm
IP protection class	IP20
Protection class	II
Voltage type	AC
Circlip	without circlip
Adjustability	swivelling
Energy efficiency class	A++ to A
Length	82 mm
Width	82 mm
Swivel angle	20 °
circuit type secondary side	parallel conduction