



recessed spot

Artikel-Nr. 12355023



1.0 m	0.7 0.7	1191.1
2.0 m	1.4 1.4	297.8
3.0 m	2.1 2.0	132.3
4.0 m	2.8 2.7	74.4
5.0 m	3.5 3.4	47.6
	Ø (m)	E0(0°) [lx]

recessed spot, chrom, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Steel / Silicone rubber / Plastic, IP protection class: according to DIN EN 60529 IP65, Protection class: (EN 61140) III, current: 350 mA, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 650lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 38°, Adjustability: swivelling, without operating, Type of dimming: other, . This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12355023
Stand:	21.04.2021 17:44

colour of light	3000 K
Colour	chrome
length	82 mm
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Aluminium / Steel / Silicone rubber / Plastic
version	Plug&Play
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	other

Built-in diameter	68 mm
Built-in depth	50 mm
Current	350 mA
Luminous flux	650 lm
IP protection class	IP65
Protection class	III
Adjustability	swivelling
length	82 mm
Width	82 mm
Swivel angle	30 °
circuit type	series conduction