


LED-Einbaudownlight FUNIL

Artikel-Nr. 12242173



LED-Einbaudownlight FUNIL, white. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 350 mA, Power: 12,2W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 1.200lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 32°, Adjustability: not adjustable, without operating, Type of dimming: other, .

Artikel-Nr.	12242173
price	106.40 €
Stand:	01.09.2020 23:52
Discount group	Discount group 1

colour of light	3000 K
Colour	white
Radiation angle	32 °
amount of light sources / fittings	1 Qty
material	Aluminium / Plastic
version	Plug&Play
Power	12,2 W
Lamp type	LED
Colour rendering	CRI > 90
Type of dimming	other

Outer diameter	115 mm
Built-in diameter	105 mm
Built-in depth	85 mm
Current	350 mA
Luminous flux	1,200 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	not adjustable
circuit type secondary side	series conduction