


recessed spot

Artikel-Nr. 12418173



recessed spot, white. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, current: 500 mA, Power: 9,3W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 700lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 32°, Adjustability: rotating and swivelling, without operating, Type of dimming: other, .

Artikel-Nr.	12418173	Applications
price	87.90 €	HOME LIVING OFFICE COMMUNICATION HOTEL INDUSTRY
Stand:	02.09.2020 02:48	GASTRONOMY
Discount group	Discount group 1	

colour of light	3000 K
Colour	white
Radiation angle	32 °
amount of light sources / fittings	1 Qty
material	Aluminium / Plastic
Power	9,3 W
Lamp type	LED
Colour rendering	CRI > 90
Type of dimming	other
Built-in diameter	98 mm

Built-in depth	60 mm
Current	500 mA
Luminous flux	700 lm
IP protection class	IP20
Protection class	III
Voltage type	DC
Adjustability	rotating and swivelling
Length	105 mm
Width	105 mm
Swivel angle	40 °
circuit type secondary side	series conduction