


LED-Anbaudownlight
Artikel-Nr. 12068173

Licht.
 Für Generationen.



LED-Anbaudownlight, white, round. Surface mounting, Ceiling-mounted. . Lamp holder: without, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, material: Aluminium / Plastic, IP protection class: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 12,1 W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 680.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 120.0 °, With operating gear: Yes, Type of dimming: switchable, Energy efficiency class: A++ to A, This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12068173
price	142.00 €
Stand:	28.08.2019 10:17

colour of light	3000 K
Colour	white
Radiation angle	120 °
amount of light sources /	1 Qty
material	Aluminium / Plastic
Power	12,1 W
Lamp type	LED
shipping	inkl. Konverter zum Anschluss
Colour rendering	CRI > 80
Type of dimming	switchable

Outer diameter	100 mm
voltage	230V AC 50Hz
Luminous flux	680 lm
IP protection class	IP20
Protection class	I
Voltage type	AC
Energy efficiency class	A++ to A
Height-depth	70.0 mm
circuit type secondary side	parallel conduction