



LED-Einbaudownlight, IP65

**Artikel-Nr. 13368073**



1.0 m	0.7 0.7	1173.2
2.0 m	1.4 1.4	283.3
3.0 m	2.1 2.0	130.4
4.0 m	2.8 2.7	73.3
5.0 m	3.5 3.4	46.9
	Ø (m)	E0(0°) [lx]

LED-Einbaudownlight IP65, white. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: Plug&Play, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP65\*, Protection class: (EN 61140) III, current: 350 mA, Power: 6W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 640lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 38°, Adjustability: not adjustable, without operating, Type of dimming: other, . This luminaire contains incorporated and non-exchangeable LED light sources.

<b>Artikel-Nr.</b>	<b>13368073</b>	<b>Applications</b>
<b>price</b>	84.90 €	HOME   LIVING OFFICE   COMMUNICATION HOTEL INDUSTRY
<b>Stand:</b>	01.09.2020 23:22	GASTRONOMY
<b>Discount group</b>	Discount group 1	

colour of light	3000 K
Colour	white
Radiation angle	38 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
version	Plug&Play
Power	6 W
Lamp type	LED
Colour rendering	CRI > 80
Type of dimming	other

Outer diameter	90 mm
Built-in diameter	75 mm
Built-in depth	50 mm
Current	350 mA
Luminous flux	640 lm
IP protection class	IP65*
Protection class	III
Voltage type	DC
Circlip	without circlip
Adjustability	not adjustable
circuit type secondary side	series conduction