


LED-Anbaustrahler BLOKK, IP65  
**Artikel-Nr. 60112103**



LED-Anbaustrahler BLOKK, IP65, black, square. Surface mounting, Floor-mounted. Mounting method: Surface mounting, Place of installation: Floor-mounted, material: Aluminium / Glass, IP protection class: according to DIN EN 60529 IP65, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 22W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 2.030lm, Colour temperature: 3000K, Radiation angle: 36°, Adjustability: swivelling, With operating gear, Type of dimming: switchable, .

<b>Artikel-Nr.</b>	<b>60112103</b>	<b>Applications</b>
<b>price</b>	339.00 €	HOME   LIVING SPA   WELLNESS INDUSTRY   CRAFT HOTEL
<b>Stand:</b>	09.07.2020 07:56	INDUSTRY   GASTRONOMY EDUCATION   CULTURE

colour of light	3000K
Colour	black
Radiation angle	36 °
amount of light sources / fittings	1 Qty
material	Aluminium / Glass
Power	22 W
Lamp type	LED
shipping	Inkl. Konverter zum Anschluss an 230 V-Netzspannung, schaltbar und 2.000 mm Anschlussleitung.
Colour rendering	CRI > 80

Type of dimming	switchable
voltage	230V AC 50Hz
Luminous flux	2,030 lm
Impact strength	IK07
IP protection class	IP65
Protection class	I
Voltage type	AC
Adjustability	swivelling
Length	110 mm
Width	110 mm
Height	132 mm
Swivel angle	90 °
circuit type secondary side	parallel conduction