




LED-Einbaudownlight HYBRIDE, V4A, IP67
Artikel-Nr. 12664223



LED-Einbaudownlight HYBRIDE, V4A, IP67, edelstahl. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Stainless steel / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP67, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 17W, amount of light sources / fittings: 1.0 Stk, Luminous flux: 2.010lm, Farbtemperatur: 3000K, Colour of light: white, Radiation angle: 34°, Adjustability: not adjustable, With operating gear, Type of dimming: switchable, .

Artikel-Nr. 12664223
Stand: 25.11.2020 11:27

colour of light	3000
Colour	stainless steel
Radiation angle	34 °
amount of light sources / fittings	1 Qty
material	Stainless steel / Aluminium / Glass
Power	17 W
Lamp type	LED
shipping	inkl. Konverter zum Anschluss an 230 V-Netzspannung, schaltbar und 5.000 mm Anschlussleitung

Colour rendering	CRI > 80
Type of dimming	switchable
Outer diameter	215 mm
Built-in diameter	205 mm
Built-in depth	185 mm
voltage	230V AC 50Hz
Luminous flux	2,010 lm
Impact strength	IK09
IP protection class	IP67
Protection class	I
Voltage type	AC
Adjustability	not adjustable
circuit type secondary side	parallel conduction