




LED-Einbaudownlight HYBRIDE, V4A, IP67
Artikel-Nr. 12664223

Licht.
 Für Generationen.



LED-Einbaudownlight HYBRIDE, V4A, IP67, stainless steel. In a compact design, for installation in tool-less rapid assembly systems. . Lamp holder: without, Mounting method: Flush mounting, Place of installation: Ceiling-mounted, material: Stainless steel / Aluminium / Glass, IP protection class: according to DIN EN 60529 IP67, Protection class: (EN 61140) I, voltage: 230V AC 50Hz, Power: 17 W, Luminous flux: 2010.0 lm, colour of light: 3000 K, Colour of light: white, Radiation angle: 34.0 °, Adjustability: not adjustable, With operating gear: Yes, Type of dimming: switchable, Energy efficiency class: A++ to A,

| | |
|--------------------|------------------|
| Artikel-Nr. | 12664223 |
| price | 410.00 € |
| Stand: | 27.08.2019 12:57 |

| | |
|---------------------------|-------------------------------|
| colour of light | 3000 K |
| Colour | stainless steel |
| Radiation angle | 34 ° |
| amount of light sources / | 1 Qty |
| material | Stainless steel / Aluminium |
| Power | 17 W |
| Lamp type | LED |
| shipping | inkl. Konverter zum Anschluss |
| Colour rendering | CRI > 80 |
| Type of dimming | switchable |
| Outer diameter | 215 mm |

| | |
|-----------------------------|---------------------|
| Built-in diameter | 205 mm |
| Built-in depth | 185 mm |
| voltage | 230V AC 50Hz |
| Luminous flux | 2,010 lm |
| Impact strength | IK09 |
| IP protection class | IP67 |
| Protection class | I |
| Voltage type | AC |
| Adjustability | not adjustable |
| Energy efficiency class | A++ to A |
| circuit type secondary side | parallel conduction |