# BRUMBERG

### **FIBATEC LED fiber projector**

Article no. 9419W







#### Tender

LED fiber projector.Comprising: 1 x projector - 3.6 W LED (L 145 x W 80 x H 70 mm), housing material: steel, housing color: black, including Lamp: 3 x LED (3 x 1.2 W) white or warm-white, including 1,500 mm connection cable with Schuko plug, including converter for connection with the 230-V mains voltage, without fan (thus no noise generation) Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 3 W, Colour temperature: 4.000 K, Light colour: White, With control gear: Yes, Control: on/off.

Article data	
Article no.	9419W
GTIN	4250047749646
Series name	FIBATEC
Short description	LED fiber projector
Material	Aluminium / Steel / Plastic
Colour	Black
Length	145 mm
Width	80 mm
Hight	70 mm
Inner diameter of fibre holder	30 mm
Weight	1.240 kg
Length of the connection line	1,500 mm

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 04.03.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

## BRUMBERG

## FIBATEC LED fiber projector

Article no. 9419W

Light. For Generations.

Lighting technology	
Light generator output	3 W
Colour temperature	4.000 K
Light colour	White
Colour rendering	CRI > 80
Adjustable color temperature	No

Operating technology of the luminaire	
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	
Degree of protection	IP20
Ambient temperature	0 up to 40 °C
Control	on/off
Length of the connection line	1,500 mm
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service
bub change possible	technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50,000 h

Packing data	
Gross weight	1.5 kg
Length of packaging	270 mm
Packaging width	270 mm
Packaging hight	120 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.