
### FERU LED surface-mounted spotlight, on/off switchable


Article no. 12063173

## BRUMBERG

Light. For Generations.







ж		$\sim$	LDT-Data
690lm	38°	230V	15-X

#### Tender

LED surface-mounted spotlight, on/off switchable, Round.Luminaire diameter 85.0 mm, Hight 95.0 mm Weight 0.599 kg,Reflector silver with rotattionssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a glass transparent cover.Luminous flux 690 lm, Power 1 x 8 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Aluminium / Glass, Colour: White structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20, .With electronic driver, on/off switchable.

Article data	
Article no.	12063173
GTIN	4250047798637
Series name	FERU
Short description	LED surface-mounted spotlight, on/off switchable
Material	Aluminium / Glass
Colour	White
Type of surface	Structure
Shape	Round
Outer diameter	85 mm
Hight	95 mm
Scope of delivery	Incl. converter for connection to the 230-V mains voltage
Weight	0.599 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 18.01.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

# **BRUMBERG**

### FERU LED surface-mounted spotlight, on/off switchable

Article no. 12063173

Light. For Generations.

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	690 lm
System efficiency	86 lm/W
Colour rendering	CRI > 80
Reflector	High-gloss
Reflector colour	silver
Beam angle	38°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	8 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	
Degree of protection	IP20
Dimmable	No
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	25°
stamp	UKCA
Material cover	Glass transparent

Packing data		
Gross weight	0.669 kg	
Length of packaging	115 mm	
Packaging width	115 mm	
Packaging hight	120 mm	
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.	
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you	
	support recycling or other forms of re-use. In that way you help to take care and to avoid that	
	harmful substances get into the environment.	

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 18.01.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/