


LED surface mounted downlight, IP54

Artikel-Nr. 12076173



LED surface mounted downlight, IP54, white, square. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP54, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 450lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 30°, Adjustability: Not adjustable, With control gear: Yes, control: on/off.

Artikel-Nr.	12076173
Stand:	25.10.2021 15:54

Colour temperature	3000 K
Colour	White
Length	70 mm
Beam angle	30 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Power	7 W
Lamp	LED
scope of delivery	Incl. converter for connection to the 230-V mains voltage

Colour rendering	CRI > 80
Control	on/off
Voltage	230V AC 50Hz
Degree of protection	IP54
Protection class	I
Adjustability	Not adjustable
Length	70 mm
Width	70 mm
Aufbauhöhe	85 mm
Circuit type	Parallel conduction