


LED recessed downlight, IP44

Artikel-Nr. 12110023



LED recessed downlight, IP44, chrome, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp optimized for installation in furniture and wood-based materials. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Die-cast zinc / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Voltage: 12V, Power: 3.4W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 255lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 60°, Adjustability: Not adjustable, With control gear: No, control: Dimming depending on driver. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12110023
Stand:	20.07.2021 22:50

Colour of light	3000 K
Colour	Chrome
Length	64 mm
Beam angle	60 °
Amount of light sources / fittings	1 Qty
Material	Die-cast zinc / Plastic
Power	3,4 W
Lamp	LED
Shipping	Including 2,000 mm connecting cable
Colour rendering	CRI > 80

control	Dimming depending on driver
Built-in diameter	56 mm
Installation depth	14 mm
Voltage	12V
Degree of protection	IP44*
Protection class	III
Adjustability	Not adjustable
Length	64 mm
Width	64 mm
Height	3 mm
Circuit type	Parallel conduction