


LED recessed downlight, IP44

**Artikel-Nr. 12128023**



LED recessed downlight, IP44, chrome, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp optimized for installation in furniture and wood-based materials. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Die-cast aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP44\*, Protection class: (EN 61140) III, Voltage: 12V, Power: 5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 400lm, Colour temperature: 2.900 K, Light colour : White, Beam angle: 60°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

<b>Artikel-Nr.</b>	<b>12128023</b>
<b>Stand:</b>	25.10.2021 20:17

Colour temperature	2900 K
Colour	Chrome
Length	75 mm
Beam angle	60 °
Amount of light sources / fittings	1 Qty
Material	Die-cast aluminium / Plastic
Power	5 W
Lamp	LED
scope of delivery	Including 2,000 mm connecting cable
Colour rendering	CRI 85

Control	Dimming depending on driver
Built-in diameter	68 mm
Installation depth	14 mm
Voltage	12V
Degree of protection	IP44*
Protection class	III
Adjustability	Not adjustable
Length	75 mm
Width	75 mm
Aufbauhöhe	3 mm
Circuit type	Parallel conduction