



LED recessed spot, IP65, dim2warm

**Artikel-Nr. 12444253**



| 1.0 m | 0.7 0.7 | 1649.8      |
|-------|---------|-------------|
| 2.0 m | 1.4 1.4 | 412.4       |
| 3.0 m | 2.1 2.0 | 183.3       |
| 4.0 m | 2.8 2.7 | 103.1       |
| 5.0 m | 3.5 3.4 | 66.0        |
|       | Ø (m)   | E0(0°) [lx] |

LED recessed spot, IP65, dim2warm, alu, round. In a compact design, for installation in tool-less rapid assembly systems. If the lamp is dimmed, the color temperature is reduced. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Silicone rubber / Plastic, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) III, Current: 350 mA, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 900lm, Colour temperature: from 1.800 K up to 3.000 K, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

|                    |                  |
|--------------------|------------------|
| <b>Artikel-Nr.</b> | <b>12444253</b>  |
| <b>Stand:</b>      | 26.10.2021 03:12 |

|                                    |   |
|------------------------------------|---|
| Colour temperature                 | 3000 K - 1800 K                               |
| Colour                             | Alu   |
| Beam angle                         | 38 °  |
| Amount of light sources / fittings | 1 Qty   |
| Material                           | Aluminium / Steel / Silicone rubber / Plastic |
| Lamp holder                        | Plug&Play                                     |
| Power                              | 12 W  |
| Lamp                               | LED   |
| Colour rendering                   | CRI > 90                                      |

|                      |                             |
|----------------------|-----------------------------|
| Control              | Dimming depending on driver |
| Outer diameter       | 82 mm                       |
| Built-in diameter    | 68 mm                       |
| Installation depth   | 84 mm                       |
| Current              | 350 mA                      |
| Degree of protection | IP65                        |
| Protection class     | III                         |
| Adjustability        | Pivoted                     |
| Swivel angle         | 30 °                        |
| Circuit type         | Series conduction           |