




LED recessed downlight BOWL

Artikel-Nr. 12527073



LED recessed downlight BOWL, white, round. In a compact design, for installation in tool-less rapid assembly systems Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 970lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 100°, Adjustability: Not adjustable, With control gear: No, control: Dimming depending on driver.

Artikel-Nr.	12527073
Stand:	20.07.2021 12:45

Colour of light	3000 K
Colour	White
Beam angle	100 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Lamp holder	Plug&Play
Power	12 W
Lamp	LED
Colour rendering	CRI > 80

control	Dimming depending on driver
Outer diameter	136 mm
Built-in diameter	120 mm
Installation depth	50 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Circuit type	Series conduction