




LED recessed downlight HYBRIDE, V4A, IP67

Artikel-Nr. 12671223



LED recessed downlight HYBRIDE, V4A, IP67, stainless steel, square. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Stainless steel / Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP67, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 11W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 550lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 117°, Adjustability: Not adjustable, With control gear: Yes, control: on/off.

Artikel-Nr.	12671223
Stand:	19.07.2021 11:33

Colour of light	3000 K
Colour	Stainless steel
Length	135 mm
Beam angle	117 °
Amount of light sources / fittings	1 Qty
Material	Stainless steel / Aluminium / Glass
Power	11 W
Lamp	LED
Shipping	Incl. converter for connection to the 230-V mains voltage, on/off and 5,000 mm connecting cable
Colour rendering	CRI > 80

control	on/off
Built-in width	125 mm
Built-in length	125 mm
Installation depth	145 mm
Voltage	230V AC 50Hz
Luminous flux	550 lm
Impact resistance	IK09
Degree of protection	IP67
Protection class	I
Adjustability	Not adjustable
Length	135 mm
Width	135 mm
Height	126 mm
Circuit type	Parallel conduction