
LED converter 350 mA, trailing-edge phase dimmable

Article no. 17663020

Light. For Generations.

BRUMBERG







Tender

LED converter 350 mA, trailing-edge phase dimmable, , Rectangular. This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz, Power: 7 W, Dimmable: Yes, Control: Trailing-edge phase.

Article data		
Article no.	17663020	
GTIN	4251433918448	
Short description	LED converter 350 mA, trailing-edge phase dimmable	
Material	Plastic	
Shape	Rectangular	
Length	110 mm	
Width	50 mm	
Hight	19 mm	
Scope of delivery	Plug&Play version with 110 mm P&P output cable	
Weight	0.100 kg	

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 22.04.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

LED converter 350 mA, trailing-edge phase dimmable

Article no. 17663020

Light. For Generations.

BRUMBERG

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	50 Hz
Frequency max	60 Hz
Output current	350 mA
Protection class	
Degree of protection	IP20
max. no. lights on B16 A	250
Starting current	1A (15,2 μs)
Power min	2.8 W
Power max.	7 W
Output_ripple_current	20
Suitable for emergency lighting	No
Control	Trailing-edge phase
Flicker-free	Yes
Enviroment temprature (ta)	0°C up to 40°C
Measure point (tc)	max. +80 °C
Average nominal lifespan	50000 h
Version	Plug&Play + connection box
Efficiency	0.78
Power factor	0.9

Packing data	
Gross weight	0.141 kg
Length of packaging	95 mm
Packaging width	75 mm
Packaging hight	95 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that
	harmful substances get into the environment.