



LED recessed downlightset, IP65, on/off

Artikel-Nr. 38149073



1.0 m	0.710.7	934.9
2.0 m	1.411.4	233.7
3.0 m	2.112.0	103.9
4.0 m	2.812.7	58.4
5.0 m	3.513.4	37.4
Ø (m)		E0(0°) [lx]

LED recessed downlightset, IP65, on/off, white, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, on/off switchable, dimensions of converter: L 68 x W 35 x H 21 mm . Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Cast iron / Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP65*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 540lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Not adjustable, With control gear: Yes, Control: on/off.

Artikel-Nr.	38149073
Stand:	25.10.2021 21:25

Colour temperature	3000 K
Colour	White
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Cast iron / Aluminium / Glass / Plastic
Power	6 W
Lamp	LED
Colour rendering	CRI > 80
Control	on/off

Outer diameter	80 mm
Built-in diameter	68 mm
Installation depth	65 mm
Voltage	230V AC 50Hz
Degree of protection	IP65*
Protection class	II
Circlip	Without circlip
Adjustability	Not adjustable
Aufbauhöhe	5 mm
Circuit type	Parallel conduction