
BRUMBERG

MIRROR LED wall surface mounted mirror luminaire, IP44

Article no. 58312003

Light. For Generations.











Tende

LED wall surface mounted mirror luminaire, IP44, Rectangular., Luminaire width 500.0 mm, Hight 1000.0 mm Weight 11.5 kg, with rotattionssymmetrical, deep, wide distributed light intensity.Luminous flux 1.788 lm, Power 1 x 24 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 90, Rated life time L70/B50 at 25 °C: 60.000 h, Housing material: Crystal plate glass / Aluminium, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP44, .With electronic driver, on/off switchable.

| Article data | |
|-------------------|---|
| Article no. | 58312003 |
| GTIN | 4251433921578 |
| Series name | MIRROR |
| Short description | LED wall surface mounted mirror luminaire, IP44 |
| Material | Crystal plate glass / Aluminium |
| Shape | Rectangular |
| Width | 500 mm |
| Hight | 1000 mm |
| Weight | 11.500 kg |

BRUMBERG

MIRROR LED wall surface mounted mirror luminaire, IP44

Article no. 58312003

Light. For Generations.

| Lighting technology | |
|------------------------------|-----------|
| Colour temperature | 3.000 K |
| Light colour | White |
| Luminous flux | 1,788 lm |
| System efficiency | 74 lm/W |
| Colour rendering | CRI > 90 |
| Reflector | Without |
| Light sharing | Symmetric |
| Adjustable color temperature | No |

| Operating technology of the luminaire | |
|---------------------------------------|--|
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequenz max. | 50 Hz |
| Lamp | LED |
| Lamp holder | Without fitting |
| Protection class | |
| Degree of protection | IP44 |
| Dimmable | No |
| Control | on/off |
| Pulls change possible | The light source of this luminaire may only be replaced by the manufacturer or a service |
| Bulb change possible | technician commissioned by him or a similarly qualified person. |
| Rated life time L70/B50 at 25 °C | 60,000 h |

| Mounting technology | |
|-----------------------|------------------|
| Mounting method | Surface mounting |
| Place of installation | Wall-mounted |
| Adjustability | Not adjustable |
| stamp | UKCA |

| Packing data | |
|-------------------------|---|
| Gross weight | 12 kg |
| Length of packaging | 530 mm |
| Packaging width | 1,030 mm |
| Packaging hight | 60 mm |
| | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. |
| Disposal at end of life | By disposing of electrical waste and other old or defective electronics separately, you |
| | support recycling or other forms of re-use. In that way you help to take care and to avoid that |
| | harmful substances get into the environment. |