
## BRUMBERG


## MIKOL LED floor luminaire, microprismatic cover, with indirect light component

Article no. 77453694

Light. For Generations.







자	$\sim$	LOT-Data
12,000lm	230V	15-21

## Tender

LED floor luminaire, microprismatic cover, with indirect light component, Square.Luminaire length 610.0 mm, Luminaire width 280.0 mm, Hight 1986.0 mm Weight 18.65 kg, with rotattionssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a plastic, opal cover.Luminous flux 12.000 lm, Power 2 x 100 W, Light colour neutral white, Correlated color temprature (CCT) 4.000 K, Colour rendering index CRI > 80, Rated life time L80/B10 at 25 °C: 50.000 h, Housing material: Aluminium / Steel / Plastic, Colour: Silver structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20, .With electronic driver, on/off switchable.

Article data	
Article no.	77453694
GTIN	4251433983019
Series name	MIKOL
Short description	LED floor luminaire, microprismatic cover, with indirect light component
Material	Aluminium / Steel / Plastic
Colour	Silver
Type of surface	Structure
Shape	Square
Length	610 mm
Width	280 mm
Hight	1986 mm
Scope of delivery	incl. supply line 2.500 mm with Schuko angle plug
Weight	18.650 kg

All technical data as well as, weight and measurements are based on rated values and had been carefully prepared. We reserve the right to make technical changes which are are important in progressing. Product pictures are examples and can vary from the original. Subject to errors. Date 24.01.2024 Orders are placed under our general terms and conditions under https://www.brumberg.com/en/terms-and-conditions/general-terms-and-conditions-of-sale/

## MIKOL LED floor luminaire, microprismatic cover, with indirect light component

Article no. 77453694

Light. For Generations.

**BRUMBERG** 

Lighting technology	
Colour temperature	4.000 K
Light colour	White
Light output	Direct/Indirect
Luminous flux	12,000 lm
System efficiency	120 lm/W
Colour rendering	CRI > 80
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	100 W
Voltage type	AC
AC nominal voltage max	230 V
Frequenz max.	50 Hz
Lamp	LED not changeable
Lamp holder	Without fitting
Protection class	
Degree of protection	IP20
Control	on/off, PUSH-Dimm, Presence detector, Daylight detector
Bulb change possible	No

Mounting technology	
Mounting method	Surface mounting
Place of installation	Floor-mounted
Adjustability	Not adjustable
Material cover	Plastic, opal

Packing data	
Gross weight	20 kg
Length of packaging	2,300 mm
Packaging width	490 mm
Packaging hight	130 mm
	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.
Disposal at end of life	By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.